

## SPECIFICATIONS

|                                                      |                       |
|------------------------------------------------------|-----------------------|
| Rated thermal input                                  | 5,9 kW                |
| Efficiency                                           | 84 %                  |
| Smoke flue diameter                                  | 180 mm                |
| Min. thrust (under pressure) for rated thermal input | 12 Pa                 |
| Fuel gas temperature                                 | 215 °C                |
| Volume of fuel gas                                   | 4,9 g/s               |
| CO emissions in fuel gas (at 13 % O <sub>2</sub> )   | 0,0943 %              |
| Dust in the fuel gas (at 13 % O <sub>2</sub> )       | 18 mg/Nm <sup>3</sup> |
| Volume of fuel per hour                              | 1,84 kg/h             |
| Fuel                                                 | wood (beech logs)     |
| Weight                                               | 250 kg                |



## LIST OF SPARE PARTS


### Glass



750 x 468 mm

### Carcon stones

1. Front bottom
2. Back bottom
3. Back
4. Right side
5. Left side
6. Deflector
7. Carcon blend



# BEF PASSIVE V 8


BLOWER DOOR  
TEST

ČSN EN  
13229

eco  
design

[www.befhome.com](http://www.befhome.com)

## TECHNICAL DRAWING



## BEF PASSIVE V 8

BLOWER DOOR  
TEST

ČSN EN  
13229

eco  
design

[www.befhome.com](http://www.befhome.com)